



F-10

Heavy Duty Two Post Lifts 10,000 lbs. Capacity

Features:

- 3-stage front and 2-stage rear arms
- Hydraulic cylinders in each column:
 - Direct pull lifting technology
 - Top mounted
 - Full stroke
 - Cylinder rod concealed inside carriage
- Single point lock release
- Includes adapter extensions and storage bracket
- Five year structural, 18 month parts, and 60 day labor warranty
- ALL certified



Model Shown:
FWD F10N100MBL
10,000 lbs. capacity

Specifications	F10N100MBL
Capacity*	10,000 lbs. (4535kg)
Rise	76-1/8" (1933mm)
Overall Height	143" (3632mm)
Overall Width	131" or optional 137" (3327-4380mm)
Drive through clearance	99" or optional 105" (2515-2667mm)
Overhead switch height	137-1/4" (3486mm)
Front reach (Min./Max.)	24-1/2" / 44-3/8" (621mm/1127mm)
Rear reach (Min./Max.)	36" / 58" (914mm/1473mm)
Min./Max. adapter height	3-5/8" (219mm) w/no adapter extension 8-5/8" (792mm) w/5" adapter extension
Width inside column	109" or optional 115" (2769mm/2921mm)
Voltage/Amps	208/230, 15 amps; 208/230, 16 amps
Motor Phase*	1ph/2HP/50Hz; 1ph/2HP/60Hz
Ceiling height required	144" (3658mm)

Specifications subject to change without notice or liability.


*3-phase available at additional cost Available in red

Low-Profile Adapter Design:

The F10 features low-profile, oversized pads with multiple extensions to raise most vehicles on the road today. Includes four (each) adapter extensions at 3.5" and 5"



5" ADAPTER 3.5" ADAPTER



996 Industrial Drive
Madison, IN 47250

Engineered to perform...Built to last!

Phone: 800.423.1722

Fax: 812.273.7329

www.forwardlift.com



Lit# Forward i10_F10_Cutsheet_2016.01

©2016 Vehicle Service GroupSM

Printed in the U.S.A. All rights reserved. Unless otherwise indicated, Forward Lift, Vehicle Service GroupSM, Dover and all other trademarks are property of Dover Corporation and its affiliates.

