



Brand: BendPak
Model(s): P-6B Surface Mount Model / P-6FB Flush-Mount Model
Description: 6,000-Lb. Capacity Low-Rise Pit Lifts

Specifically designed and engineered for quick oil-change facilities, the P-6B or P-6FB easily convert ordinary fast-lube pits into wheel-service bays making wheel rotations and brake service a natural addition. Add thousands of dollars to your profit line every month with these revolutionary pit-lifts that are loaded with standard features including a commercial duty 1-1/2 HP electric-hydraulic power unit, dual hydraulic cylinders, precision flow-divider, simple push-button controls and remote pneumatic safety locks. Installation materials, hydraulic hoses and mounting hardware are included with each unit. Optional LR-4A lift arms adapt fast and easy and allow safe lifting of vehicles using manufacturer designated lift points.

With their 6,000 lbs. lifting capacity, these rugged lifts will easily handle virtually every automobile, light truck and SUV. With their clear-center design, the P-6B surface mount, or the P-6FB flush mount model installs over your existing pit without interfering with your lube bay opening.



Features;

- 6,000 lbs. lifting capacity
- Easily convert fast-lube pits into wheel service work bays
- Mounts outside the pit rail without interfering with center work area
- Model P-6FB flush-mount model provides recessed drive-over option
- Heavy duty 1-1/2 HP electric-hydraulic power unit
- Electronic push-button controls allow smooth, single hand operation
- Automatic multi-position safety locks with air release deliver safe, remote operation
- Powder coat finish
- Durable rubber-topped pad surface and rubber lift blocks provide quick set-up
- ETL-certified



MODEL	P-6B	P-6FB
Style:	Surface Mount	Flush Mount-Recessed
Lifting Capacity:	6,000 lbs. / 2722 Kg.	6,000 lbs. / 2722 Kg.
Lifting Height (Less Lift Blocks):	26" / 660 mm.	26" / 660 mm.
Lifting Height (With Lift Blocks):	29" / 737 mm.	29" / 737 mm.
Overall Pad Length	53" / 1346 mm.	53" / 1346 mm.
Overall Width	18" / 457 mm.	18" / 457 mm.
Overall Length	81" / 2057 mm.	78" / 1981 mm.
Lowered Height:	4" / 102 mm.	4" / 102 mm.
Lifting Time:	35 / Seconds	35 / Seconds
Motor (*)	110-220 VAC / 60 Hz. / 1Ph.	110-220 VAC / 60 Hz. / 1Ph.
* Special Voltages Available Upon Request.		
The design, material and specifications are subject to change without notice.		

