



**Brand:** BendPak  
**Model(s):** XPR-12FDL  
**Description:** 12,000-lb. Capacity Two-Post Lift / Direct-Drive Floorplate

**Features**

- 12,000-lb lifting capacity
- Open-top eliminates overhead obstruction
- Wide drive-thru configuration
- Single-piece columns
- Single-point safety release
- Oversized 53" tall carriage for superior strength and durability
- Electric / hydraulic power system
- Self-lubricating dura-glide UHMW polyethylene carriage bearings
- Safety locks in each column spaced every 3"
- Automatic arm restraints
- Heavy-duty 1/2" aircraft-quality equalizer cables
- Oversized 6" diameter steel cable sheaves reduce cable fatigue
- Versatile drop-in contact pads with stackable 8-piece truck and van adapters
- Frame cradle pads come standard
- Triple-telescoping, low-profile arms
- ETL approved



**ALL ADAPTERS INCLUDED STANDARD**



8 Piece Adapter Set

Rubber Contact Pads

Frame Cradle Pads

MODEL	XPR-12FDL
Lifting Capacity*	12,000 Lbs. / 5443 Kg.
*Max Capacity / Front Axle	6,000 lbs. / 2722 Kg.
*Max Capacity / Rear Axle	6,000 lbs. / 2722 Kg.
<b>A</b> - Height Overall:	144" / 3403 mm.
<b>B</b> - Width Overall (Outside of Base Plate):	155" / 3937 mm.
<b>C</b> - Width (Outside of Columns):	146" / 3708 mm.
<b>D</b> - Cover Height:	2" / 51 mm.
<b>E</b> - Inside Columns:	118" / 2997 mm.
<b>F</b> - Reach (Front Arm Min.):	39" / 991 mm.
<b>G</b> - Reach (Front Arm Max.):	59" / 1499 mm.
<b>H</b> - Reach (Rear Arm Min.):	39" / 991 mm.
<b>I</b> - Reach (Rear Arm Max.):	59" / 1499 mm.
<b>J</b> - Min. Pad Height:	5" / 127 mm.
<b>K</b> - Rise:	69" / 1753 mm.
<b>L</b> - Max Lift Height (Pad Only):	74" / 1880 mm.
<b>M</b> - Max Lift Height (6" Adapter):	80" / 2032 mm.
<b>N</b> - Drive-Thru Clearance:	103" / 2616 mm.
Motor (*)	220 VAC / 60 Hz. 1Ph.
Time of full Rise:	55 Seconds
Max Load Per Arm:	3,000Lbs. / 1361 Kg.

\* Special Voltages Available Upon Request.

